

1965-74 CHEVELLE POWER STEERING GEARS

YEAR	ALPHA CODE	ORIGINAL APPLICATION	GEAR RATIO	EFFORT	VALVE #	TRAVEL
1965 -66		A-6 cyl	17.5:1	15-21	5583/2428	43deg 30min
		A-8 cyl	17.5:1	15-21	5583/2428	43deg 30min
		A-SS Interim	15:1	15-21	5583	43deg 30min
		A-8 cyl Interim	17.5:1	15-21	5583	43deg 30min
1967		A-8 cyl	17.5:1	15-21	5583	43deg 30min
1968	AH	A-8 cyl	17.5:1	15-21	5583	43deg 30min
1969	AH	A-8 cyl	17.5:1	15-21	5583	43deg 30min
	AU	A-SS	16-12.4:1	15-21	5583	43deg 30min
1970	BA	A-8 cyl	16-12.4:1	15-21	5583	43deg 30min
	BH	A-8 SWagon	17.5:1	15-21	5583	43deg 30min
	CE	A-8 SWagon Interim	17.5:1	15-21	5583	43deg 30min
	CF	A-8 Interim	16-12.4:1	15-21	5583	43deg 30min
1971-72	CA	A-Mk IV	16-13:1	12-17	7837	41deg 30min
	CL	A All	16-13:1	12-17	7837	41deg 30min
1973	GA	A SWagon	16-13:1	12-17	7837	41deg 30minL/44deg 30minR
	JT	A	16-13:1	12-17	7837	39deg 45minL/41 deg 30minR
	WU	A-Special SS	15-13:1	14-20	4930	38deg 45minL/40deg 30minR
	XA	A	16-13:1	14-20	4930	41deg 30min
	XB	A SWagon	16-13:1	14-20	4930	44deg 30min
	WZ	A-SS	15-13:1	17-22	8369	40deg 30min
1974	EP	A	16-13:1	12-17	7837	39deg 45minL/41 deg 30minR
	GD	A SWagon	16-13:1	12-17	7837	41deg 30minL/44deg 30minR
	ER	A-Special SS	15-13:1	14-20	6464/4930	38deg 45minL/40deg 30minR